



## DECLARATION OF PERFORMANCE

No. FB251-CPR-02-05-2023

### Stopgap 850

Unique identification code of the product-type:	Stopgap 850
Intended use/es:	Repair mortar (PCC) for non-structural repair of concrete structures with low performance requirements in buildings and civil engineering works; Principle 3, Method 3.1
Manufacturer:	F. Ball and Co. Ltd., Churnetside Business Park, Station Road, Cheddleton, Leek, Staffordshire, ST13 7RS, UK
Approved body/ies:	Not applicable

Declared performance/s:			
Essential characteristics	Performance	Assessment of verification of constancy of performance	Designated standard
Reaction to fire	NPD	System 4	EN 1504-3:2005
Compressive strength	Class R2 $\geq 15$ MPa	System 4	EN 1504-3:2005
Chloride ion content	$\leq 0,05\%$		
Adhesive bond	$\geq 0,8$ MPa		
Thermal compatibility; Part 1: Freeze-thaw	$\geq 0,8$ MPa		
Skid resistance	Class III $> 55$ Wet		
Capillary absorption	$\leq 0,5$ kg.m <sup>-2</sup> .h <sup>-0,5</sup>		
Dangerous substances	comply with 5.4		

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Stuart Whiteley  
Development Manager

At Leek on 26 February 2024

**Note:** Information on the content of substances concerning the Registration, Evaluation, Authorisation, and Restriction of Chemicals (UK REACH), is indicated in the safety data sheet available on the website together with this current declaration of performance.