



STYCCOBOND F1

Rubber Latex Adhesive

INTRODUCTION

STYCCOBOND F1 is a natural rubber latex based product designed for use as a seaming and sealing adhesive for carpets. Its creamy consistency makes it suitable for application with brush or applicator.

STYCCOBOND F1 is for use with a suitable joining tape for seaming traditional and hessian backed carpets and for sealing edges of traditional carpets to prevent fibre loss.

SURFACE PREPARATION

Proper subfloor preparation is essential to the correct installation of any floorcovering. Subfloors must be sound, smooth, dry and free from any contaminants which will affect adhesion. For detailed information request our **F. Ball Subfloor Preparation Guide**.

DAMP SUBFLOORS

The Relative Humidity (RH) of the subfloor can be measured using the F. Ball Digital Hygrometer. Where the RH value is greater than 75% the appropriate STOPGAP waterproof surface membrane should be applied.

SMOOTHING

To ensure a level surface on which to adhere to, uneven and irregular surfaces should be suitably prepared using the appropriate STOPGAP smoothing compounds.

ADHESIVE APPLICATION

Seaming of carpets: Ensure that both edges are cut cleanly and are free from loose fibres, dirt, grease etc. Apply an even coat of adhesive to the back of the carpet and the surface of the joining tape. Allow to partially dry before pressing the surfaces firmly together, using a hand roller.

Edge sealing of traditional carpets: Remove any loose fibres, then apply adhesives to the edge of the carpet using a brush. Allow to dry before the carpet is stretched over the grippers.

PRECAUTIONS

Do not stretch the carpet until the adhesive has fully dried, premature stretching of the carpet will result in the seams opening up.

TECHNICAL INFORMATION

| | |
|---------------------|------------|
| Colour | White |
| Consistency | Liquid |
| Open time (Approx.) | 20 minutes |



FEATURES

- For seaming and sealing
- Can be used to prevent fibre loss

STORAGE

Store between 5°C and 30°C.
Protect from frost.

PACK SIZE

5 litre bottle

STANDARDS

All aspects of the installation of floorcoverings should be in accordance with the requirements of the relevant British Standard Code of Practice i.e. BS 5325 (Installation of textile floorcoverings) and supplementary specifications

HEALTH & SAFETY

This product is not classified. Persons with a known allergy to natural rubber latex are advised not to use this product. Relevant safety data sheets and advice given can be found at www.f-ball.com.

Alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Site conditions vary, to ensure this product is suitable and to confirm this data sheet is current please contact our Technical Service Department.

F. Ball and Co. Ltd.

Churnetside Business Park,
Station Road, Cheddleton,
Leek, Staffordshire.
ST13 7RS UK
Tel: +44 (0) 1538 361633
www.f-ball.com
mail@f-ball.co.uk