Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: STYCCOBOND F61

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Adhesive for floors. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

F. Ball and Co. Ltd.
Churnetside Business Park, Station Road
ST13 7RS Cheddleton - Leek - England
Phone: +44(0) 1538 361633
msds@f-ball.co.uk
www.f-ball.com
F. Ball and Co (Europe) Limited
109 Cork Street,
The Liberties,
D08 X279,
Dublin 8

Dublin 8, Co. Dublin, Ireland

1.4 Emergency telephone number: +353 1 809 2166

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 2: Flammable liquids, Category 2, H225 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 2: H361d - Suspected to damage the foetus.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

- CONTINUED ON NEXT PAGE -

BALL

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61



SECTION 2: HAZARDS IDENTIFICATION (continued)

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P260: Do not breathe vapours

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313: Get medical advice/attention.

Supplementary information:

Contains Formaldehyde, oligomeric reaction products with phenol, Rosin.

Substances that contribute to the classification

Toluene; Ethyl acetate; Hydrocarbons, C6, isoalkanes, <5% n-hexane; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

UFI: 0F60-U0E2-C009-087D

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration	
CAS:	108-88-3	Toluene(1) ATP CLP00				
	203-625-9 601-021-00-3 01-2119471310-51- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STO RE 2: H373; STOT SE 3: H336 - Danger	T (1) (8) (8)	10 - <30 %	
CAS: EC:	141-78-6	Ethyl acetate(1)		ATP CLP00		
Index:	205-500-4 607-022-00-5 I: 01-2119475103-46- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	<u>(1)</u>	10 - <30 %	
CAS:	64742-49-0	Hydrocarbons, C6, is	oalkanes, <5% n-hexane(1)	Self-classified		
	931-254-9 Non-applicable : 01-2119484651-34- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	(1) (a) (b) (b)	10 - <30 %	
CAS:	64742-49-0 927-510-4 Non-applicable 01-2119475515-33- XXXX	Hydrocarbons, C7, n-	Self-classified			
		Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	(1) (a) (b) (b)	2.5 - <10 %	
CAS:	9003-35-4	Formaldehyde, oligo	meric reaction products with phenol(1)	Self-classified		
	500-005-2 Non-applicable 01-2120735197-51- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Sens. 1: H317 - Warning	•	2.5 - <10 %	
CAS:	8050-09-7	Rosin ⁽¹⁾		ATP CLP00		
	232-475-7 650-015-00-7 01-2119480418-32- XXXX	Regulation 1272/2008	Skin Sens. 1: H317 - Warning	•	<1 %	
CAS: EC:	119-47-1	6,6´-di-tert-butyl-2,	2´-methylenedi-p-cresol(1)	Self-classified		
Index:	204-327-1 604-095-00-5 01-2119496065-33- XXXX	Regulation 1272/2008	Repr. 2: H361 - Warning	&	<1 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) Page 2/15

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61



SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) **Page 3/15**

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137 / The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) Page 4/15



STYCCOBOND F61



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

	Identification	Occ	Occupational exposure limits			
Toluene (1)		WEL (8h)	50 ppm	191 mg/m ³		
CAS: 108-88-3	EC: 203-625-9	WEL (15 min)	100 ppm	384 mg/m ³		
Ethyl acetate		WEL (8h)	200 ppm	734 mg/m ³		
CAS: 141-78-6	EC: 205-500-4	WEL (15 min)	400 ppm	1468 mg/m ³		
Rosin		WEL (8h)		0.05 mg/m ³		
CAS: 8050-09-7	EC: 232-475-7	WEL (15 min)		0.15 mg/m ³		

⁽¹⁾ Skin

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 108-88-3	Dermal	Not relevant	Not relevant	384 mg/kg	Not relevant
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³
Ethyl acetate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 141-78-6	Dermal	Not relevant	Not relevant	63 mg/kg	Not relevant
EC: 205-500-4	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64742-49-0	Dermal	Not relevant	Not relevant	13964 mg/kg	Not relevant
EC: 931-254-9	Inhalation	Not relevant	Not relevant	5306 mg/m ³	Not relevant
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64742-49-0	Dermal	Not relevant	Not relevant	300 mg/kg	Not relevant
EC: 927-510-4	Inhalation	Not relevant	Not relevant	2085 mg/m ³	Not relevant
Formaldehyde, oligomeric reaction products with phenol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 9003-35-4	Dermal	Not relevant	Not relevant	28 mg/kg	Not relevant
EC: 500-005-2	Inhalation	Not relevant	Not relevant	98.7 mg/m ³	Not relevant
Rosin	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 8050-09-7	Dermal	Not relevant	Not relevant	2.131 mg/kg	Not relevant
EC: 232-475-7	Inhalation	Not relevant	Not relevant	Not relevant	10 mg/m ³
6,6 '-di-tert-butyl-2,2 '-methylenedi-p-cresol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 119-47-1	Dermal	Not relevant	Not relevant	0.36 mg/kg	Not relevant
EC: 204-327-1	Inhalation	Not relevant	Not relevant	1.25 mg/m ³	Not relevant

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Not relevant	Not relevant	8.13 mg/kg	Not relevant
CAS: 108-88-3	Dermal	Not relevant	Not relevant	226 mg/kg	Not relevant
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56.5 mg/m ³	56.5 mg/m ³
Ethyl acetate	Oral	Not relevant	Not relevant	4.5 mg/kg	Not relevant
CAS: 141-78-6	Dermal	Not relevant	Not relevant	37 mg/kg	Not relevant
EC: 205-500-4	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Oral	Not relevant	Not relevant	1301 mg/kg	Not relevant
CAS: 64742-49-0	Dermal	Not relevant	Not relevant	1377 mg/kg	Not relevant
EC: 931-254-9	Inhalation	Not relevant	Not relevant	1131 mg/m³	Not relevant
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Oral	Not relevant	Not relevant	149 mg/kg	Not relevant
CAS: 64742-49-0	Dermal	Not relevant	Not relevant	149 mg/kg	Not relevant
EC: 927-510-4	Inhalation	Not relevant	Not relevant	447 mg/m ³	Not relevant
Formaldehyde, oligomeric reaction products with phenol	Oral	Not relevant	Not relevant	10 mg/kg	Not relevant
CAS: 9003-35-4	Dermal	Not relevant	Not relevant	10 mg/kg	Not relevant
EC: 500-005-2	Inhalation	Not relevant	Not relevant	14.8 mg/m ³	Not relevant
Rosin	Oral	Not relevant	Not relevant	1.065 mg/kg	Not relevant
CAS: 8050-09-7	Dermal	Not relevant	Not relevant	1.065 mg/kg	Not relevant
EC: 232-475-7	Inhalation	Not relevant	Not relevant	Not relevant	Not relevant

- CONTINUED ON NEXT PAGE -

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) **Page 5/15**



STYCCOBOND F61



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol	Oral	0.65 mg/kg	Not relevant	0.13 mg/kg	Not relevant
CAS: 119-47-1	Dermal	Not relevant	Not relevant	0.13 mg/kg	Not relevant
EC: 204-327-1	Inhalation	Not relevant	Not relevant	0.22 mg/m ³	Not relevant

PNEC:

Identification				
Toluene	STP	13.61 mg/L	Fresh water	0.68 mg/L
CAS: 108-88-3	Soil	2.89 mg/kg	Marine water	0.68 mg/L
EC: 203-625-9	Intermittent	0.68 mg/L	Sediment (Fresh water)	16.39 mg/kg
	Oral	Not relevant	Sediment (Marine water)	16.39 mg/kg
Ethyl acetate	STP	650 mg/L	Fresh water	0.24 mg/L
CAS: 141-78-6	Soil	0.148 mg/kg	Marine water	0.024 mg/L
EC: 205-500-4	Intermittent	1.65 mg/L	Sediment (Fresh water)	1.15 mg/kg
	Oral	0.2 g/kg	Sediment (Marine water)	0.115 mg/kg
Formaldehyde, oligomeric reaction products with phenol	STP	Not relevant	Fresh water	0.172 mg/L
CAS: 9003-35-4	Soil	0.0284 mg/kg	Marine water	0.0172 mg/L
EC: 500-005-2	Intermittent	1.72 mg/L	Sediment (Fresh water)	0.647 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.0647 mg/kg
Rosin	STP	1000 mg/L	Fresh water	0.002 mg/L
CAS: 8050-09-7	Soil	0 mg/kg	Marine water	0 mg/L
EC: 232-475-7	Intermittent	0.016 mg/L	Sediment (Fresh water)	0.007 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.001 mg/kg
6,6´-di-tert-butyl-2,2´-methylenedi-p-cresol	STP	Not relevant	Fresh water	Not relevant
CAS: 119-47-1	Soil	Not relevant	Marine water	Not relevant
EC: 204-327-1	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	0.01 g/kg	Sediment (Marine water)	Not relevant

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



STYCCOBOND F61



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
+	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	- (0)	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 73.75 % weight V.O.C. density at 20 °C: Not relevant

Average carbon number: 5.81

Average molecular weight: 90.07 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Liquid

Viscous

Solvent

Solvent

Not relevant *

Volatility:

Boiling point at atmospheric pressure: 85 °C Vapour pressure at 20 °C: 8928 Pa

Vapour pressure at 50 °C: 31496.72 Pa (31.5 kPa)

Evaporation rate at 20 °C: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) **Page 7/15**

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61

Not relevant *



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Product description:

Density at 20 °C: Not relevant *

Relative density at 20 °C: 0.9

Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: >20.5 mm²/s Concentration: Not relevant * Not relevant * pH: Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant * Solubility properties: Not relevant * Decomposition temperature: Not relevant *

Flammability:

Flash Point: -17 °C

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Not relevant *
306 °C

Not available

Upper flammability limit:

Not available

Particle characteristics:

Melting point/freezing point:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Not relevant *

Corrosive to metals:

Not relevant *

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Not relevant *

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Not relevant *

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) **Page 8/15**

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61







SECTION 10: STABILITY AND REACTIVITY (continued)

10.5 Incompatible materials:

Acids Water		Oxidising materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Toluene (3); Hydrocarbons, C6, isoalkanes, <5% n-hexane (3); Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected to damage the foetus
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant



STYCCOBOND F61



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Specific toxicology information on the substances:

Identification	Ac	cute toxicity	Genus
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28.1 mg/L (4 h)	Rat
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	>20 mg/L	
Formaldehyde, oligomeric reaction products with phenol	LD50 oral	>2000 mg/kg	
CAS: 9003-35-4	LD50 dermal	>2000 mg/kg	
EC: 500-005-2	LC50 inhalation	>5 mg/L	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	LD50 oral	>2000 mg/kg	
CAS: 64742-49-0	LD50 dermal	>2000 mg/kg	
EC: 931-254-9	LC50 inhalation	>20 mg/L	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 oral	>2000 mg/kg	
CAS: 64742-49-0	LD50 dermal	>2000 mg/kg	
EC: 927-510-4	LC50 inhalation	>20 mg/L	
Rosin	LD50 oral	4100 mg/kg	Rat
CAS: 8050-09-7	LD50 dermal	>2000 mg/kg	
EC: 232-475-7	LC50 inhalation	>5 mg/L	
6,6´-di-tert-butyl-2,2´-methylenedi-p-cresol	LD50 oral	5700 mg/kg	Rat
CAS: 119-47-1	LD50 dermal	>2000 mg/kg	
EC: 204-327-1	LC50 inhalation	>5 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus	
Toluene	LC50	5.5 mg/L (96 h)	Oncorhynchus kisutch	Fish	
CAS: 108-88-3	EC50	3.78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean	
EC: 203-625-9	EC50	Not relevant			
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	LC50	Not relevant			
CAS: 64742-49-0	EC50	3.87 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 931-254-9	EC50	55 mg/L (72 h)	Scenedesmus subspicatus	Algae	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LC50	>1 - 10 mg/L (96 h)		Fish	
CAS: 64742-49-0	EC50	>1 - 10 mg/L (48 h)		Crustacean	
EC: 927-510-4	EC50	>1 - 10 mg/L (72 h)		Algae	
Rosin	LC50	150 mg/L (96 h)	Brachydanio rerio	Fish	
CAS: 8050-09-7	EC50	238 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 232-475-7	EC50	185 mg/L (72 h)	Selenastrum capricornutum	Algae	

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) **Page 10/15**



STYCCOBOND F61



SECTION 12: ECOLOGICAL INFORMATION (continued)

Chronic toxicity:

Identification	Concentration		Species	Genus
Ethyl acetate NOEC		9.65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC 2.4 mg/L		Daphnia magna	Crustacean
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		Not relevant		
CAS: 64742-49-0 EC: 927-510-4	NOEC	0.17 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	De	gradability	Biodegra	adability
Toluene	BOD5	2.5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Not relevant	Period	14 days
EC: 203-625-9	BOD5/COD	Not relevant	% Biodegradable	100 %
Ethyl acetate	BOD5	1.36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1.69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0.8	% Biodegradable	83 %
Hydrocarbons, C6, isoalkanes, <5% n-hexane	BOD5	Not relevant	Concentration	100 mg/L
CAS: 64742-49-0	COD	Not relevant	Period	28 days
EC: 931-254-9	BOD5/COD	Not relevant	% Biodegradable	98 %
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	BOD5	Not relevant	Concentration	Not relevant
CAS: 64742-49-0	COD	Not relevant	Period	14 days
EC: 927-510-4	BOD5/COD	Not relevant	% Biodegradable	95 %
Formaldehyde, oligomeric reaction products with phenol	BOD5	0.5 g O2/g	Concentration	Not relevant
CAS: 9003-35-4	COD	Not relevant	Period	Not relevant
EC: 500-005-2	BOD5/COD	Not relevant	% Biodegradable	Not relevant
Rosin	BOD5	Not relevant	Concentration	Not relevant
CAS: 8050-09-7	COD	Not relevant	Period	28 days
EC: 232-475-7	BOD5/COD	Not relevant	% Biodegradable	32 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification		Bioaccumulation potential		
Toluene	BCF	90		
CAS: 108-88-3	Pow Log	2.73		
EC: 203-625-9	Potential	Moderate		
Ethyl acetate	BCF	30		
CAS: 141-78-6	Pow Log	0.73		
EC: 205-500-4	Potential	Moderate		
Hydrocarbons, C6, isoalkanes, <5% n-hexane	BCF	501		
CAS: 64742-49-0	Pow Log	3.6		
EC: 931-254-9	Potential	High		
Formaldehyde, oligomeric reaction products with phenol	BCF	8142		
CAS: 9003-35-4	Pow Log	3.56		
EC: 500-005-2	Potential	Very High		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Toluene	Koc	178	Henry	672.8 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2.793E-2 N/m (25 °C)	Moist soil	Yes
Ethyl acetate	Koc	59	Henry	13.58 Pa·m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2.324E-2 N/m (25 °C)	Moist soil	Yes
Formaldehyde, oligomeric reaction products with phenol	Koc	636795	Henry	Not relevant
CAS: 9003-35-4	Conclusion	Immobile	Dry soil	No
EC: 500-005-2	Surface tension	Not relevant	Moist soil	No

- CONTINUED ON NEXT PAGE -

Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) **Page 11/15**

STYCCOBOND F61



SECTION 12: ECOLOGICAL INFORMATION (continued)

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code Description		Waste class (Regulation (EU) No 1357/2014)	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous	

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

14.1 UN number or ID number: UN1133 **ADHESIVES** 14.2 UN proper shipping name:

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: ΙΙ 14.5 Environmental hazards: Nο 14.6 Special precautions for user

Special regulations: 640D Tunnel restriction code: D/E

> Physico-Chemical properties: see section 9 Limited quantities: 5 I

14.7 Maritime transport in bulk according to IMO

instruments:

Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

Version: 19 (Replaced 18) Date of compilation: 07/03/2023 Revised: 09/07/2024 Page 12/15

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61







SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1133 **14.2 UN proper shipping name:** ADHESIVES

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: II
14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: Not relevant
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9

Limited quantities: 5 I

Segregation group: Not relevant **14.7 Maritime transport in bulk** Not relevant

according to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number or ID number: UN113314.2 UN proper shipping name: ADHESIVES

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: II14.5 Environmental hazards: No14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Maritime transport in bulk** Not relevant

according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): 6,6 '-di-tert-butyl-2,2 '-methylenedi-p-cresol (119-47-1)
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- —tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61



SECTION 15: REGULATORY INFORMATION (continued)

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885 Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.

H361d: Suspected to damage the foetus.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Repr. 2: H361d - Suspected to damage the foetus.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method

STOT SE 3: Calculation method

STOT RE 2: Calculation method

Repr. 2: Calculation method

Skin Sens. 1: Calculation method

Aquatic Chronic 3: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F61



SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 07/03/2023 Revised: 09/07/2024 Version: 19 (Replaced 18) Page 15/15