BALL

IMPACT TAPE
Contact Adhesive On A Roll

INTRODUCTION
IMPACT TAPE is a double sided tape of pressure sensitive adhesive on a fine webbing carrier. It has high plasticiser resistance and is also resistant to wet cleaning.

APPLICATIONS
For bonding a wide range of dimensionally stable smooth faced materials to wall surfaces of plaster, wood, concrete, metal and ceramic tiles.

APPLICATION TECHNIQUES
Surfaces must be smooth, clean, dry and free of dust. Very absorbent surfaces such as untreated plaster should be primed with STOPGAP P131.

Apply the tape directly to the material to be bonded.

Remove the release paper, position on the wall and apply firm pressure to obtain the maximum performance from the tape.

Corners and joints should be re-inforced by applying Impact Tape directly to the wall on all internal and external mitres. Cut the material to fit the mitre before fitting into position.

Full information is available from the F. Ball Technical Service Department.

FEATURES
• Rapid application

• Plasticiser resistant

• Low odour

• No health and safety hazard in normal use

SPECIFICATION
• Tape width: 25mm, 50mm and 85mm

• Roll size: 50 metres

SHELF LIFE
24 months in the original packaging stored under cool conditions.

TOOLS
Hand roller.

HEALTH & SAFETY
This product is not classified. Relevant safety data sheets and advice given can be found at www.f-ball.com.

Alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Site conditions vary, to ensure this product is suitable and to confirm this data sheet is current please contact our Technical Service Department.

F. Ball and Co. Ltd.
Churnetside Business Park,
Station Road, Cheddleton,
Leek, Staffordshire.
ST13 7RS UK
Tel: +44 (0) 1538 361633
www.f-ball.com
mail@f-ball.co.uk

FOR FURTHER INFORMATION ABOUT F. BALL PRODUCTS OR MORE DETAILED TECHNICAL ASSISTANCE, VISIT F-BALL.COM OR CALL (+44) 01538 361633

QCP 4784