



STOPGAP P141

Primer for Non-Absorbent Surfaces

INTRODUCTION

STOPGAP P141 is an acrylic primer designed to promote adhesion and application characteristics of STOPGAP smoothing compounds to non-absorbent subfloors. STOPGAP P141 contains recycled uPVC pulver that dries to a hard, textured surface to enhance bond performance.

STOPGAP P141 is coloured yellow to provide the user with visual control of coverage uniformity.

STOPGAP P141 is recommended for use over non-absorbent surfaces including STOPGAP waterproof surface membranes, ceramic tiles, treated power floated concrete and prepared steel.

STOPGAP P141 is also recommended prior to the application of STOPGAP 600 over non-absorbent surfaces when applied at thicknesses greater than 20mm.

It is suitable for use for use in marine applications as part of an IMO system.

PREPARATION

Floor surfaces must be suitably prepared: sound, smooth, dry (below 85% in accordance with ASTM F2170 insitu probe method) and free from contaminants that may prevent adhesion. The temperature of the surface must be above 10°C when the primer is applied to the subfloor and underfloor heating must be off for at least 48 hours before, during and after application. Ensure the subfloor is dry and incorporates an effective damp proof membrane.

For detailed information, request the **F. Ball Subfloor Preparation Guide**.

TECHNICAL INFORMATION

Colour	Yellow
Coverage Rates (Approx.)	Applied neat to non-absorbent surfaces: 65m ² Rates will vary based on the condition of the subfloor
Drying Time (Approx.)	From 15 minutes at 20°C on non-absorbent subfloors

COVERAGE

PACK SIZE	COVERAGE PER UNIT
5 litres neat	65m ² (max)

Coverage rates will depend on the condition and absorbency of the subfloor.

FEATURES

- Textured finish
- Fast drying
- Pigmented to provide coverage control
- Suitable for use with F. Ball marine applications

SCAN QR CODE TO VIEW PRODUCT DEMO



APPLICATION/COVERAGE

SHAKE WELL BEFORE USE. DO NOT DILUTE.

Apply the primer directly to the floor at approximately 13m² per litre. Do not extend coverage as this may affect adhesion properties. Avoid puddling in depressions as this will affect drying times.

DRYING TIME

From 15 minutes at 20°C.

Higher temperatures will reduce drying times and lower temperatures, damp ambient conditions and poor airflow will significantly extend this time. The use of a fan is recommended to reduce drying times.

PRECAUTIONS

Avoid excessive trafficking of the subfloor once the primer has dried.

TOOLS

- Short or medium pile roller
- Wash with warm water immediately after use and store in a polythene bag.

STORAGE

Store between 5°C and 25°C. Protect from frost.

PACK SIZE

5 litre bottle

SHELF LIFE

12 months in unopened containers and stored under good conditions.

HEALTH & SAFETY

This product is not classified. Relevant safety data sheets and advice given can be found at www.f-ball.com.

Alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Site conditions vary, to ensure this product is suitable and to confirm this data sheet is current please contact our Technical Service Department.

**FOR FURTHER INFORMATION
ABOUT F. BALL PRODUCTS OR
MORE DETAILED TECHNICAL
ASSISTANCE, VISIT F-BALL.COM
OR CALL +44 (0)1538 361633**



F. Ball and Co. Ltd.

Churnetside Business Park,
Station Road, Cheddleton,
Leek, Staffordshire.
ST13 7RS UK
Tel: +44 (0) 1538
www.f-ball.com
mail@f-ball