

NIEUW

STOPGAP



**BAL**  
**STOPGAP**  
**P114**  
 Primer for Non-Absorbent Surfaces  
 SHAKE WELL BEFORE USE

**STOPGAP P114** is an acrylic primer designed to promote adhesion and application characteristics of STOPGAP smoothing compounds to non-absorbent substrates. STOPGAP P114 contains recycled PVC powder that dries to a hard, textured surface to enhance bonding to the substrate.

STOPGAP P114 is also recommended prior to the application of STOPGAP smoothing compounds to surfaces when applied at thicknesses greater than 20mm. It is suitable for use over normal underfloor heating and coverage uniformly.

**PREPARATION**  
 Floors surfaces must be suitably prepared: sound, smooth, dry (<75% RH) and free from contaminants that may prevent adhesion. The temperature of the floor must be a minimum of 5°C degrees when the primer is applied to the subfloor and underfloor heating must be off for at least 48 hours before, during and after application. Ensure the subfloor is dry and incorporates an effective damp proof membrane. For detailed information, request our Subfloor Preparation Guide.

**TOOLS**  
 Short or medium pile roller. Wash with warm water immediately after use and store in a polythene bag.

**APPLICATION/COVERAGE**  
 SHAKE WELL BEFORE USE  
 Apply the primer directly to the floor at approximately 13m<sup>2</sup> per litre. Do not extend coverage as this may affect adhesion properties. Avoid puddling in depressions as this will affect drying times.

**DRYING TIME**  
 Drying Times - From 15 minutes at 20°C degrees. Lower temperatures, damp ambient conditions and poor airflow will significantly extend this time. The use of a fan is recommended to reduce drying times.

**SHELF LIFE**  
 12 months in unopened containers.

**STORAGE**  
 To avoid damage store in a cool, dry place away from frost.

**HEALTH AND SAFETY**  
 Contains 1,2-BEHAZDIONE  
 METHYL-4-ISOTHIAZOL

Sheet and follow the advice given - where can be found on www.f-ball.co.uk. Alternatively, advice can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Manufactured in the UK by  
**F. Ball and Co. Ltd.**  
 Charnock Business Park, Sutton Road  
 Cheddleton, Leek, Staffordshire ST13 7RS UK  
 Tel: +44 (0) 1538 361623 Fax: +44 (0) 1538 361622  
 www.f-ball.co.uk

**5 litres**

5 038464 131409

Perfekte primer voor niet-absorberende vloeren ...