Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: STOPGAP SRS RESIN

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Concrete surface finisher. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

F. Ball and Co. Ltd.

Churnetside Business Park, Station Road ST13 7RS Cheddleton - Leek - England

Phone: +44(0) 1538 361633

msds@f-ball.co.uk www.f-ball.com

F. Ball and Co (Europe) Limited

109 Cork Street, The Liberties, D08 X279,

Dublin 8,

Co. Dublin,

Ireland

1.4 Emergency telephone number: +353 1 809 2166

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning





Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P264: Wash thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313: Get medical advice/attention.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH205: Contains epoxy constituents. May produce an allergic reaction. Contains Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane.

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) **Page 1/12**

BALL **♣**

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 2: HAZARDS IDENTIFICATION (continued)

UFI: 7X60-V0JF-6008-Y9QS

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of organic substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification					
CAS: EC:	1675-54-3 216-823-5	Bis-[4-(2,3-epoxipropoxi)phenyl]propane(1) ATP CLP00					
Index:	603-073-00-2 01-2119456619-26- XXXX	Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	25 - <50 %				
CAS:	933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane(1) Self-classified					
Index: Non- REACH: 01-2:	618-939-5 Non-applicable 01-2119463471-41- XXXX	Regulation 1272/2008 Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning 📢	25 - <50 %				
CAS:	108-65-6	2-methoxy-1-methylethyl acetate ⁽²⁾ ATP ATP01					
EC: Index: REACH:	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	<1 %				

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Bis-[4-(2,3-epoxipropoxi)phenyl]propane CAS: 1675-54-3 EC: 216-823-5	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 2/12

⁽²⁾ Substance with a Union workplace exposure limit

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 4: FIRST AID MEASURES (continued)

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 3/12

BALL

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 7: HANDLING AND STORAGE (continued)

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupa	upational exposure limits		
2-methoxy-1-methylethyl acetate	WEL (8h)	50 ppm	274 mg/m ³	
CAS: 108-65-6	WEL (15 min)	100 ppm	548 mg/m ³	

DNEL (Workers):

		Short e	exposure Long exposure		xposure
Identification		Systemic	Local	Systemic	Local
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1675-54-3	Dermal	Non-applicable	Non-applicable	0.75 mg/kg	Non-applicable
EC: 216-823-5	Inhalation	Non-applicable	Non-applicable	4.93 mg/m ³	Non-applicable
Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 933999-84-9	Dermal	Non-applicable	Non-applicable	6 mg/kg	Non-applicable
EC: 618-939-5	Inhalation	10.57 mg/m ³	Non-applicable	10.57 mg/m ³	0.44 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable

DNEL (General population):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	Oral	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
CAS: 1675-54-3	Dermal	Non-applicable	Non-applicable	0.0893 mg/kg	Non-applicable
EC: 216-823-5	Inhalation	Non-applicable	Non-applicable	0.87 mg/m ³	Non-applicable

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 4/12



STOPGAP SRS RESIN



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short e	exposure Long exposure		xposure
Identification		Systemic	Local	Systemic	Local
Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane	Oral	1.5 mg/kg	Non-applicable	1.5 mg/kg	Non-applicable
CAS: 933999-84-9	Dermal	1.7 mg/kg	Non-applicable	3 mg/kg	Non-applicable
EC: 618-939-5	Inhalation	5.29 mg/m ³	Non-applicable	5.29 mg/m ³	0.27 mg/m ³
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³

PNEC:

Identification				
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	STP	10 mg/L	Fresh water	0.006 mg/L
CAS: 1675-54-3	Soil	0.065 mg/kg	Marine water	0.001 mg/L
EC: 216-823-5	Intermittent	0.018 mg/L	Sediment (Fresh water)	0.341 mg/kg
	Oral	0.011 g/kg	Sediment (Marine water)	0.034 mg/kg
Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane	STP	1 mg/L	Fresh water	0.011 mg/L
CAS: 933999-84-9	Soil	0.223 mg/kg	Marine water	0.001 mg/L
EC: 618-939-5	Intermittent	0.115 mg/L	Sediment (Fresh water)	0.283 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.028 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0.635 mg/L
CAS: 108-65-6	Soil	0.29 mg/kg	Marine water	0.064 mg/L
EC: 203-603-9	Intermittent	6.35 mg/L	Sediment (Fresh water)	3.29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.329 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 5/12



STOPGAP SRS RESIN



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency meas	ure	Standards	Emergency measure	Standards
*		ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency show	ver		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0.33 % weight

V.O.C. density at 20 °C: 3.67 kg/m³ (3.67 g/L)

Average carbon number: 8.76

Average molecular weight: 120.95 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

Appearance:

Colour:

Odour:

Odour:

Not available

Not available

Not available

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: >200 °C Vapour pressure at 20 °C: 235 Pa

Vapour pressure at 50 °C: 1524.94 Pa (1.52 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1106.7 kg/m³

Relative density at 20 °C: 1.11

Dynamic viscosity at 20 °C: 140 cP

Kinematic viscosity at 20 °C:

Kinematic viscosity at 40 °C:

Concentration:

Non-applicable *

Non-applicable *

stNot relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 6/12

BALL

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

pH: Non-applicable *

Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility in water at 20 °C: Non-applicable *

Solubility properties: Non-applicable *

Decomposition temperature: Non-applicable *

Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 230 °C

Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Non-applicable *

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

STOPGAP SRS RESIN



SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Corrosivity/Irritability:
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Bis-[4-(2,3-epoxipropoxi)phenyl]propane (3); 2,6-di-tert-butyl-p-cresol (3); Solvent naphtha (petroleum), light arom.

- , < 0.1 % EC 200-753-7 (3); Naphtha (petroleum), hydrodesulphurized heavy (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Bis-[4-(2,3-epoxipropoxi)phenyl]propane	LD50 oral	>2000 mg/kg	
CAS: 1675-54-3	LD50 dermal	20000 mg/kg	Rabbit
EC: 216-823-5	LC50 inhalation	>5 mg/L	
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane	LD50 oral	3010 mg/kg	Rat
CAS: 933999-84-9	LD50 dermal	>2000 mg/kg	
EC: 618-939-5	LC50 inhalation	>20 mg/L	

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 8/12



STOPGAP SRS RESIN



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane	LC50	30 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 933999-84-9	EC50	39 mg/L (48 h)	Daphnia magna	Crustacean
EC: 618-939-5	EC50	Non-applicable		
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		

Chronic toxicity:

Identification		Concentration	Species	Genus
2-methoxy-1-methylethyl acetate	NOEC	47.5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane	BOD5	Non-applicable	Concentration	2 mg/L
CAS: 933999-84-9	COD	Non-applicable	Period	28 days
EC: 618-939-5	BOD5/COD	Non-applicable	% Biodegradable	47 %
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L
CAS: 108-65-6	COD	Non-applicable	Period	8 days
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioa	Bioaccumulation potential		
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane	BCF	4		
CAS: 933999-84-9	Pow Log	0.82		
EC: 618-939-5	Potential	Low		
2-methoxy-1-methylethyl acetate	BCF	1		
CAS: 108-65-6	Pow Log	0.43		
EC: 203-603-9	Potential	Low		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volati	lity
Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane	Кос	962	Henry	Non-applicable
CAS: 933999-84-9	Conclusion	Low	Dry soil	Non-applicable
EC: 618-939-5	Surface tension	Non-applicable	Moist soil	Non-applicable

Date of compilation: 1/23/2023 Revised: 6/6/2023 Version: 5 (Replaced 5) Page 9/12

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 12: ECOLOGICAL INFORMATION (continued)

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 03 05*	organic wastes containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number or ID number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-

di-tert-butyl-p-cresol; Solvent naphtha (petroleum), light arom. , <

0.1 % EC 200-753-7)

14.3 Transport hazard class(es): 9

Labels: 9 **14.4 Packing group:** III

14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 274, 335, 375, 601

Tunnel restriction code:

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:

- CONTINUED ON NEXT PAGE -

Safety data sheet





STOPGAP SRS RESIN



SECTION 14: TRANSPORT INFORMATION (continued)

UN3082 14.1 UN number or ID number:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-14.2 UN proper shipping name:

di-tert-butyl-p-cresol; Solvent naphtha (petroleum), light arom. , <

0.1 % EC 200-753-7)

14.3 Transport hazard class(es):

Labels: 9

III 14.4 Packing group: 14.5 Marine pollutant: Yes

14.6 Special precautions for user

335, 969, 274 Special regulations: FmS Codes: F-A, S-F Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable

14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



14.1 UN number or ID number:

11N3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-14.2 UN proper shipping name:

di-tert-butyl-p-cresol; Solvent naphtha (petroleum), light arom. , <

0.1 % EC 200-753-7)

14.3 Transport hazard class(es):

Labels: 14.4 Packing group: III

14.5 Environmental hazards: 14.6 Special precautions for user

> Physico-Chemical properties: see section 9

14.7 Maritime transport in bulk

according to IMO instruments:

Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STOPGAP SRS RESIN



SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885 Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.