

## STYCCOBOND F81 RESIN



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** STYCCOBOND F81 RESIN

Other means of identification:

Non-applicable

www.f-ball.com

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Adhesive. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

F. Ball and Co. Ltd. Churnetside Business Park, Station Road ST13 7RS Cheddleton - Leek - England Phone: +44(0) 1538 361633 msds@f-ball.co.uk

1.4 Emergency telephone number: 111

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

#### **GB CLP Regulation:**

Classification of this product has been carried out in accordance with GB CLP Regulation.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

## 2.2 Label elements:

## **GB CLP Regulation:**

## Warning





#### **Hazard statements:**

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

## **Precautionary statements:**

P264: Wash hands thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313: Get medical advice/attention.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

## **Supplementary information:**

EUH205: Contains epoxy constituents. May produce an allergic reaction.

## Substances that contribute to the classification

reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ); Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

## 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) **Page 1/11** 



## STYCCOBOND F81 RESIN



## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture of polymers, dispersants and organic compounds

**Components:** 

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )  Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	25 - <50 %
CAS:	9003-36-5	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	10 - <25 %
CAS:	68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	2.5 - <10 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

## By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

## By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

## By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

## Unsuitable extinguishing media:

Non-applicable

## 5.2 Special hazards arising from the substance or mixture:

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) Page 2/11



## STYCCOBOND F81 RESIN



## SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

## **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures:

## For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

## 6.4 Reference to other sections:

See sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

## 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) **Page 3/11** 



## **STYCCOBOND F81 RESIN**



## SECTION 7: HANDLING AND STORAGE (continued)

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

## **DNEL (Workers):**

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 25068-38-6	Dermal	Non-applicable	Non-applicable	0.75 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	Non-applicable	Non-applicable	4.93 mg/m <sup>3</sup>	Non-applicable
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 9003-36-5	Dermal	Non-applicable	Non-applicable	104.15 mg/kg	Non-applicable
EC: 500-006-8	Inhalation	Non-applicable	Non-applicable	29.39 mg/m <sup>3</sup>	Non-applicable
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68609-97-2	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
EC: 271-846-8	Inhalation	Non-applicable	Non-applicable	3.6 mg/m <sup>3</sup>	Non-applicable

## **DNEL (General population):**

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	Oral	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
CAS: 25068-38-6	Dermal	Non-applicable	Non-applicable	0.0893 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	Non-applicable	Non-applicable	0.87 mg/m <sup>3</sup>	Non-applicable
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	Oral	Non-applicable	Non-applicable	6.25 mg/kg	Non-applicable
CAS: 9003-36-5	Dermal	Non-applicable	Non-applicable	62.5 mg/kg	Non-applicable
EC: 500-006-8	Inhalation	Non-applicable	Non-applicable	8.7 mg/m <sup>3</sup>	Non-applicable
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Oral	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
CAS: 68609-97-2	Dermal	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
EC: 271-846-8	Inhalation	Non-applicable	Non-applicable	0.87 mg/m <sup>3</sup>	Non-applicable

## PNEC:

Identification				
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	STP	10 mg/L	Fresh water	0.006 mg/L
CAS: 25068-38-6	Soil	0.065 mg/kg	Marine water	0.001 mg/L
EC: 500-033-5	Intermittent	0.018 mg/L	Sediment (Fresh water)	0.341 mg/kg
	Oral	0.011 g/kg	Sediment (Marine water)	0.034 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol	STP	10 mg/L	Fresh water	0.003 mg/L
CAS: 9003-36-5	Soil	0.237 mg/kg	Marine water	0 mg/L
EC: 500-006-8	Intermittent	0.025 mg/L	Sediment (Fresh water)	0.294 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.029 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	STP	10 mg/L	Fresh water	0.106 mg/L
CAS: 68609-97-2	Soil	1.234 mg/kg	Marine water	0.011 mg/L
EC: 271-846-8	Intermittent	0.072 mg/L	Sediment (Fresh water)	307.16 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	30.72 mg/kg

## 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) Page 4/11

## **BALL**

## Safety data sheet According to UK REACH

## STYCCOBOND F81 RESIN



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding << UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

## C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

## E.- Body protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
	Anti-slip work shoes	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

## F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>→</b>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

## The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 0 % weight V.O.C. density at 20 °C: 0 kg/m $^3$  (0 g/L)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

\*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) Page 5/11



## STYCCOBOND F81 RESIN



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid Appearance: Paste Colour: Yellow Odour: Not available Odour threshold: Non-applicable \*

Volatility:

Non-applicable \* Boiling point at atmospheric pressure: Non-applicable \* Vapour pressure at 20 °C: Vapour pressure at 50 °C: <300000 Pa (300 kPa) Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

Density at 20 °C: 1466.5 kg/m<sup>3</sup>

Relative density at 20 °C: 1.31 Dynamic viscosity at 20 °C: 216000 cP Non-applicable \* Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: >20.5 mm<sup>2</sup>/s Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* Solubility properties: Non-applicable \* Decomposition temperature: Non-applicable \* Melting point/freezing point:

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Non-applicable \* Autoignition temperature: Non-applicable \* Lower flammability limit: Non-applicable \* Upper flammability limit: Non-applicable \*

**Particle characteristics:** 

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Non-applicable \* Explosive properties: Oxidising properties: Non-applicable \* Corrosive to metals: Non-applicable \* Heat of combustion: Non-applicable \* Aerosols-total percentage (by mass) of flammable Non-applicable \*

components:

Other safety characteristics:

Surface tension at 20 °C: Non-applicable \* \*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) Page 6/11

Non-applicable \*



## STYCCOBOND F81 RESIN



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

## 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

## Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Corrosivity/Irritability:
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

    IARC: Non-applicable
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) Page 7/11

## **BALL**♠

## Safety data sheet According to UK REACH

## STYCCOBOND F81 RESIN



## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

## E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	Acu	te toxicity	Genus
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 oral	>5000 mg/kg	
CAS: 9003-36-5	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LD50 oral	>5000 mg/kg	
CAS: 68609-97-2	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	LD50 oral	>5000 mg/kg	
CAS: 25068-38-6	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

## **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Toxicity:

## **Acute toxicity:**

Identification	Concentration		Species	Genus
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 25068-38-6	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 9003-36-5	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

## **Chronic toxicity:**

Identification	Concentration		Species	Genus
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	NOEC	Non-applicable		
CAS: 25068-38-6	NOEC	0.3 mg/L	Daphnia magna	Crustacean

## 12.2 Persistence and degradability:

## Substance-specific information:



## STYCCOBOND F81 RESIN



## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 25068-38-6	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

#### 12.3 Bioaccumulative potential:

#### **Substance-specific information:**

Identification	Bioaco	Bioaccumulation potential		
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	BCF	4		
CAS: 25068-38-6	Pow Log	2.8		
	Potential	Low		

## 12.4 Mobility in soil:

Not available

## 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods:

	Code	Description	Waste class
ĺ	08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

#### Type of waste:

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

## Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

## Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

## **SECTION 14: TRANSPORT INFORMATION**

#### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



**14.1 UN number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ))

**14.3** Transport hazard class(es): 9

Labels: 9

**14.4 Packing group:** III **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Tunnel restriction code: -

Physico-Chemical properties: see section 9 Limited quantities: 5 L

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Non-applicable

- CONTINUED ON NEXT PAGE -

Date of compilation: 08/03/2023 Revised: 06/06/2023 Version: 14 (Replaced 14) **Page 9/11** 

## **BALL**♠

## Safety data sheet According to UK REACH

## STYCCOBOND F81 RESIN



## SECTION 14: TRANSPORT INFORMATION (continued)

#### Transport of dangerous goods by sea:

With regard to IMDG 40-20:

**14.1 UN number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ))

14.3 Transport hazard class(es): 9

Labels: 9 **14.4 Packing group:** III

14.5 Marine pollutant:

14.6 Special precautions for user

Special regulations: 335, 969, 274
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9
Limited quantities: 5 L

Segregation group: Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

Non-applicable

## Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

**14.1 UN number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ))

**14.3 Transport hazard class(es):** 9 Labels: 9

14.4 Packing group: III
14.5 Environmental hazards: Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Non-applicable

## **SECTION 15: REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

## The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

## Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

## Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

# **BALL**

## Safety data sheet According to UK REACH

## **STYCCOBOND F81 RESIN**



## SECTION 15: REGULATORY INFORMATION (continued)

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

## SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

#### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

H319: Causes serious eye irritation.

## Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

## **GB CLP Regulation:**

Aguatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

#### Classification procedure:

Skin Irrit. 2: Calculation method Skin Sens. 1: Calculation method Aquatic Chronic 2: Calculation method Eye Irrit. 2: Calculation method

## Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### **Principal bibliographical sources:**

http://echa.europa.eu http://eur-lex.europa.eu

## **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

Date of compilation: 08/03/2023

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Revised: 06/06/2023