BALL♠

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: STYCCOBOND F84 RESIN

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Adhesive. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

F. Ball and Co. Ltd.
Churnetside Business Park, Station Road
ST13 7RS Cheddleton - Leek - England
Phone: +44(0) 1538 361633
msds@f-ball.co.uk
www.f-ball.com
F. Ball and Co (Europe) Limited

109 Cork Street, The Liberties, D08 X279, Dublin 8,

Co. Dublin, Ireland

1.4 Emergency telephone number: +44 (0) 1538 361633 Mon-Fri 08:30 - 17:00 (exc Bank Holidays)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

This product contains crystalline silica but due to its liquid state does not require classification (STOT RE)

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Precautionary statements:

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313: Get medical advice/attention.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

BALL **♣**

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 2: HAZARDS IDENTIFICATION (continued)

EUH205: Contains epoxy constituents. May produce an allergic reaction.

Contains Cashew, nutshell liq.. **UFI:** RQ60-C0G8-800S-08YK

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of polymers, dispersants and organic compounds

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | Identification | | Chemical name/Classification | Concentration |
|-------------------------|--|---|--|---------------|
| CAS: | 14808-60-7 | Quartz (1 % < RCS < 10%)(1) Self- | | |
| EC: Index: REACH: | 238-878-4 Non-applicable Non-applicable | Regulation 1272/2008 | STOT RE 2: H373 - Warning | 10 - <25 % |
| CAS: | 25068-38-6 | reaction product: bis | phenol-A-(epichlorhydrin) (MW < 700) ⁽¹⁾ ATP CLP00 | |
| EC: Index: REACH: | 500-033-5 603-074-00-8 Non-applicable | Regulation 1272/2008 | Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning | 10 - <25 % |
| CAS: | 68609-97-2 | oxirane, mono[(C12- | 14-alkyloxy)methyl] derivs.(1) ATP CLP00 | |
| EC: Index: REACH: | 271-846-8 603-103-00-4 01-2119485289-22- XXXX | Regulation 1272/2008 | Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning | 2.5 - <10 % |
| CAS: EC: | 9003-36-5 500-006-8 | Formaldehyde, oligor phenol ⁽¹⁾ | neric reaction products with 1-chloro-2,3-epoxypropane and Self-classified | |
| Index: REACH: | Non-applicable 01-2119454392-40- XXXX | Regulation 1272/2008 | Aquatic Chronic 2: H411; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning | 2.5 - <10 % |
| CAS: 8007-24-7 | | Cashew, nutshell liq. | Self-classified | |
| EC: Index: REACH: | 232-355-4 Non-applicable 01-2120038044-68- XXXX | Regulation 1272/2008 | Acute Tox. 4: H312; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1A: H317 - Danger | <1 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

| Identification | Specific concentration limit |
|----------------|---|
| | % (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 |

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878



STYCCOBOND F84 RESIN



SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

Most important symptoms and effects, both acute and delayed: 4.2

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Date of compilation: 2/28/2023 Revised: 6/6/2023 Version: 18 (Replaced 18) Page 3/12

BALL♠

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

| Identification | Occupational exposure limits | | |
|-------------------------|------------------------------|--|-----------------------|
| Quartz (1 %< RCS < 10%) | WEL (8h) | | 0.1 mg/m ³ |
| CAS: 14808-60-7 | WEL (15 min) | | |

DNEL (Workers):

| | | Short exposure | | Long exposure | |
|---|------------|----------------|----------------|------------------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 25068-38-6 | Dermal | Non-applicable | Non-applicable | 0.75 mg/kg | Non-applicable |
| EC: 500-033-5 | Inhalation | Non-applicable | Non-applicable | 4.93 mg/m ³ | Non-applicable |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 68609-97-2 | Dermal | Non-applicable | Non-applicable | 1 mg/kg | Non-applicable |
| EC: 271-846-8 | Inhalation | Non-applicable | Non-applicable | 3.6 mg/m ³ | Non-applicable |

Date of compilation: 2/28/2023 Revised: 6/6/2023 Version: 18 (Replaced 18) Page 4/12



Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| | | Short exposure | | Long exposure | |
|--|------------|----------------|----------------|-------------------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 9003-36-5 | Dermal | Non-applicable | Non-applicable | 104.15 mg/kg | Non-applicable |
| EC: 500-006-8 | Inhalation | Non-applicable | Non-applicable | 29.39 mg/m ³ | Non-applicable |

DNEL (General population):

| | | Short exposure | | Long exposure | |
|--|------------|----------------|----------------|------------------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | Oral | Non-applicable | Non-applicable | 0.5 mg/kg | Non-applicable |
| CAS: 25068-38-6 | Dermal | Non-applicable | Non-applicable | 0.0893 mg/kg | Non-applicable |
| EC: 500-033-5 | Inhalation | Non-applicable | Non-applicable | 0.87 mg/m ³ | Non-applicable |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | Oral | Non-applicable | Non-applicable | 0.5 mg/kg | Non-applicable |
| CAS: 68609-97-2 | Dermal | Non-applicable | Non-applicable | 0.5 mg/kg | Non-applicable |
| EC: 271-846-8 | Inhalation | Non-applicable | Non-applicable | 0.87 mg/m ³ | Non-applicable |
| Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol | Oral | Non-applicable | Non-applicable | 6.25 mg/kg | Non-applicable |
| CAS: 9003-36-5 | Dermal | Non-applicable | Non-applicable | 62.5 mg/kg | Non-applicable |
| EC: 500-006-8 | Inhalation | Non-applicable | Non-applicable | 8.7 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|--|--------------|----------------|-------------------------|----------------|
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | STP | 10 mg/L | Fresh water | 0.006 mg/L |
| CAS: 25068-38-6 | Soil | 0.065 mg/kg | Marine water | 0.001 mg/L |
| EC: 500-033-5 | Intermittent | 0.018 mg/L | Sediment (Fresh water) | 0.341 mg/kg |
| | Oral | 0.011 g/kg | Sediment (Marine water) | 0.034 mg/kg |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | STP | 10 mg/L | Fresh water | 0.106 mg/L |
| CAS: 68609-97-2 | Soil | 1.234 mg/kg | Marine water | 0.011 mg/L |
| EC: 271-846-8 | Intermittent | 0.072 mg/L | Sediment (Fresh water) | 307.16 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 30.72 mg/kg |
| Formaldehyde, oligomeric reaction products with 1-chloro- 2,3-epoxypropane and phenol | STP | 10 mg/L | Fresh water | 0.003 mg/L |
| CAS: 9003-36-5 | Soil | 0.237 mg/kg | Marine water | 0 mg/L |
| EC: 500-006-8 | Intermittent | 0.025 mg/L | Sediment (Fresh water) | 0.294 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0.029 mg/kg |
| Cashew, nutshell liq. | STP | 10 mg/L | Fresh water | 0.006 mg/L |
| CAS: 8007-24-7 | Soil | Non-applicable | Marine water | 0.001 mg/L |
| EC: 232-355-4 | Intermittent | Non-applicable | Sediment (Fresh water) | Non-applicable |
| | Oral | Non-applicable | Sediment (Marine water) | Non-applicable |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands $\,$

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|----------------------------|-----------|-------------------|--|
| Mandatory hand protection | Chemical protective gloves | CAT III | EN ISO 21420:2020 | Replace the gloves at any sign of deterioration. |

Date of compilation: 2/28/2023 Revised: 6/6/2023 Version: 18 (Replaced 18) **Page 5/12**



According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|--|-----------|---------------------------------|---|
| Mandatory face protection | Panoramic glasses against splash/projections. | CATII | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|----------------------|-----------|-------------------|---|
| | Work clothing | CATI | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
| | Anti-slip work shoes | CATII | EN ISO 20347:2012 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007 |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|-------------------|---|-------------------|--|
| • | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | - | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |
| Emergency shower | | Eyewash stations | |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0.99 % weight

V.O.C. density at 20 °C: 14.33 kg/m³ (14.33 g/L)

Average carbon number: 8.94

Average molecular weight: 125.91 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Description:

Paste

Reige

Odour:

Not available

Odour threshold:

Non-applicable **

Volatility:

Boiling point at atmospheric pressure: $165 \, ^{\circ}\text{C}$ Vapour pressure at 20 $^{\circ}\text{C}$: $218 \, \text{Pa}$

Vapour pressure at 50 °C: 1363.04 Pa (1.36 kPa)

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 2/28/2023 Revised: 6/6/2023 Version: 18 (Replaced 18) **Page 6/12**

BALL♠

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1447.8 kg/m³

Relative density at 20 °C: 1.27

Dynamic viscosity at 20 °C: 40000 - 60000 cP Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: >20.5 mm²/s Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas):

Non-applicable *

Autoignition temperature: 396 °C

Lower flammability limit:

Upper flammability limit:

Non-applicable *
Non-applicable *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *
Oxidising properties: Non-applicable *
Corrosive to metals: Non-applicable *
Heat of combustion: Non-applicable *
Aerosols-total percentage (by mass) of flammable Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Date of compilation: 2/28/2023 Revised: 6/6/2023 Version: 18 (Replaced 18) **Page 7/12**





STYCCOBOND F84 RESIN



SECTION 10: STABILITY AND REACTIVITY (continued)

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Not applicable | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Corrosivity/Irritability:
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Solvent naphtha (petroleum), light arom. , < 0.1 % EC 200-753-7 (3); Quartz (1 % < RCS < 10%) (1)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | A | cute toxicity | Genus |
|--|-----------------|---------------|-------|
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | LD50 oral | >2000 mg/kg | |
| CAS: 9003-36-5 | LD50 dermal | >2000 mg/kg | |
| EC: 500-006-8 | LC50 inhalation | >20 mg/L | |
| oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | LD50 oral | >2000 mg/kg | |
| CAS: 68609-97-2 | LD50 dermal | >2000 mg/kg | |
| EC: 271-846-8 | LC50 inhalation | >20 mg/L | |
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | LD50 oral | >2000 mg/kg | |
| CAS: 25068-38-6 | LD50 dermal | >2000 mg/kg | |
| EC: 500-033-5 | LC50 inhalation | >5 mg/L | |
| Quartz (1 %< RCS < 10%) | LD50 oral | >2000 mg/kg | |
| CAS: 14808-60-7 | LD50 dermal | >2000 mg/kg | |
| EC: 238-878-4 | LC50 inhalation | >5 mg/L | |
| Cashew, nutshell liq. | LD50 oral | >2000 mg/kg | |
| CAS: 8007-24-7 | LD50 dermal | >2000 mg/kg | |
| EC: 232-355-4 | LC50 inhalation | >20 mg/L | |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|--|---------------|-----------------------|---------|------------|
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | LC50 | >1 - 10 mg/L (96 h) | | Fish |
| CAS: 25068-38-6 | EC50 | >1 - 10 mg/L (48 h) | | Crustacean |
| EC: 500-033-5 | EC50 | >1 - 10 mg/L (72 h) | | Algae |
| Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol | LC50 | >1 - 10 mg/L (96 h) | | Fish |
| CAS: 9003-36-5 | EC50 | >1 - 10 mg/L (48 h) | | Crustacean |
| EC: 500-006-8 | EC50 | >1 - 10 mg/L (72 h) | | Algae |
| Cashew, nutshell liq. | LC50 | >10 - 100 mg/L (96 h) | | Fish |
| CAS: 8007-24-7 | EC50 | >10 - 100 mg/L (48 h) | | Crustacean |
| EC: 232-355-4 | EC50 | >10 - 100 mg/L (72 h) | | Algae |

Chronic toxicity:

| Identification | | Concentration | Species | Genus |
|---|------|----------------|---------------|------------|
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | NOEC | Non-applicable | | |
| CAS: 25068-38-6 EC: 500-033-5 | NOEC | 0.3 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:





STYCCOBOND F84 RESIN



SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Degradability | | Biodegradability | |
|---|---------------|----------------|------------------|----------|
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 25068-38-6 | COD | Non-applicable | Period | 28 days |
| EC: 500-033-5 | BOD5/COD | Non-applicable | % Biodegradable | 0 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential | |
|---|---------------------------|-----|
| reaction product: bisphenol-A-(epichlorhydrin) (MW < 700) | BCF | 4 |
| CAS: 25068-38-6 | Pow Log | 2.8 |
| EC: 500-033-5 | Potential | Low |

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|--|---|
| 08 04 09* | waste adhesives and sealants containing organic solvents or other hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable Article 95, REGULATION (EU) No 528/2012: Non-applicable





STYCCOBOND F84 RESIN



SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885 Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits

The Waste Regulations 2011, 2011 No. 988

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H412: Harmful to aquatic life with long lasting effects.
- H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312 - Harmful in contact with skin.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

BALL

Safety data sheet According to COMMISSION REGULATION (EU) 2020/878

STYCCOBOND F84 RESIN



SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 2/28/2023 Revised: 6/6/2023 Version: 18 (Replaced 18) Page 12/12