



# STOPGAP ISOLATOR

## JOINTING TAPE

### PRODUCT DATA

#### INTRODUCTION

**STOPGAP ISOLATOR JOINTING TAPE** is a thin metallised polypropylene tape with a solvent free, self-adhesive coating that can be used to provide extra stability to the installation of **STOPGAP ISOLATOR MEMBRANE**.

The use of this impervious tape along the seams of **STOPGAP ISOLATOR MEMBRANE** maintains moisture barrier properties and protection in damp areas.

#### APPLICATION

Ensure the **STOPGAP ISOLATOR MEMBRANE** is free from dust, dirt or any contamination that may affect adhesion. Edges must be butt jointed to ensure no gaps between sheets that could shadow through the finished floorcovering.

Apply the **STOPGAP ISOLATOR JOINTING TAPE** neatly across the joint of the two sheets ensuring approximately 25mm overlap on each sheet. Press the tape firmly to ensure full contact is maintained and ensure the tape is flat and smooth as any creases may shadow through the final floorcovering.

#### PRECAUTIONS

In certain service conditions and in conjunction with high sheen floorcoverings, the outline of the taped joints may be seen.

#### STORAGE

Store between 5°C and 30°C.  
Protect from frost

#### SHELF LIFE

24 months in unopened containers stored under good conditions.

#### TECHNICAL INFORMATION

Adhesive	Acrylic water based
Support thickness	30Micron $\pm 3\%$
Total thickness	49Micron $\pm 6\%$
Tensile strength	4.5Kg/cm $\pm 10\%$
Elongation	150% $\pm 10\%$

For further information about F. Ball products or more detailed technical assistance, please contact:

**F. Ball and Co. Ltd.**  
Churnetside Business Park  
Station Road, Cheddleton, Leek  
Staffordshire ST13 7RS  
United Kingdom

Tel: +44 (0) 1538 361633  
Email: [mail@f-ball.co.uk](mailto:mail@f-ball.co.uk)



F. Ball and Co. Ltd.