



SAFETY DATA SHEET STYCCOBOND F61

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STYCCOBOND F61

Internal identification SBF61/16

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Flooring Adhesive

Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier F.Ball and Co. Ltd.
Churnetside Business Park,
Station Road,
Cheddleton,
Leek,
Staffordshire. ST13 7RS
Tel: 01538 361633 Mon-Fri 8.30am-5.00pm (Exc Bank Holidays)
Fax: 01538 361622
E.mail: msds@f-ball.co.uk

1.4. Emergency telephone number

Emergency telephone 01538 361633 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 3 - H412

Human health Contains a substance with possible risk of harm to the unborn child. Irritating and degreasing to skin. Irritating to eyes.

Environmental Solvent contamination of drains, surface waters and land. VOC emissions to air. Potential fire and explosion hazard. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical The product is highly flammable.

2.2. Label elements

STYCCOBOND F61

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapour/ spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P313 Get medical advice/ attention.

Contains

TOLUENE, ETHYL ACETATE, NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN

Supplementary precautionary statements

P243 Take action to prevent static discharges.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|----------------------|
| NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN | 10-30% |
| CAS number: 64742-49-0 | EC number: 265-151-9 |
| Classification | |
| Muta. 1B - H340 | |
| Carc. 1B - H350 | |
| Asp. Tox. 1 - H304 | |

STYCCOBOND F61

| | |
|---|----------------------|
| TOLUENE | 10-30% |
| CAS number: 108-88-3 | EC number: 203-625-9 |
| Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 | |
| ETHYL ACETATE | 10-30% |
| CAS number: 141-78-6 | EC number: 205-500-4 |
| Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | |

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|--|
| General information | Remove affected person from source of contamination. |
| Inhalation | Move affected person to fresh air at once. Get medical attention. |
| Ingestion | Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately. |
| Skin contact | Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing. |
| Eye contact | Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | Vapours may cause headache, fatigue, dizziness and nausea. May cause an asthma-like shortness of breath. May cause damage to organs through prolonged or repeated exposure. |
| Ingestion | May cause discomfort if swallowed. |
| Skin contact | Skin irritation. Prolonged skin contact may cause redness and irritation. May cause an allergic skin reaction. |
| Eye contact | Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|-----------------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

STYCCOBOND F61

| | |
|---------------------------------------|--|
| Suitable extinguishing media | Extinguish with foam, carbon dioxide or dry powder. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

5.2. Special hazards arising from the substance or mixture

| | |
|--------------------------------------|---|
| Specific hazards | In case of fire toxic gases/vapours may be formed. The product is highly flammable. |
| Hazardous combustion products | Toxic gases or vapours. |

5.3. Advice for firefighters

| | |
|--|---|
| Protective actions during firefighting | Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. |
| Special protective equipment for firefighters | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|--|
| Personal precautions | Evacuate non-essential personnel from the spill area. No smoking, sparks, flames or other sources of ignition near spillage. Take precautionary measures against static discharge and arcing from electrical equipment. Avoid inhalation of vapours and contact with skin and eyes. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. |
|-----------------------------|--|

6.2. Environmental precautions

| | |
|----------------------------------|--|
| Environmental precautions | Do not discharge into drains or watercourses or onto the ground. |
|----------------------------------|--|

6.3. Methods and material for containment and cleaning up

| | |
|--------------------------------|--|
| Methods for cleaning up | Contain and absorb spillage with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste. |
|--------------------------------|--|

6.4. Reference to other sections

| | |
|------------------------------------|--|
| Reference to other sections | For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13. |
|------------------------------------|--|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|--------------------------|---|
| Usage precautions | Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Vapours may accumulate on the floor and in low-lying areas. Do not use in confined spaces without adequate ventilation and/or respirator. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. |
|--------------------------|---|

7.2. Conditions for safe storage, including any incompatibilities

| | |
|----------------------------|--|
| Storage precautions | Stored in tightly closed original container in a cool, dry well ventilated place at a temperature between 5 deg C and 30 deg C. Protect against physical damage and/or friction. Keep away from heat, static or electrical sparks, open flame and direct sunlight. Avoid contact with oxidising agents. Keep separate from food, feedstuffs, fertilisers and other sensitive material. |
|----------------------------|--|

7.3. Specific end use(s)

| | |
|----------------------------|---|
| Specific end use(s) | The identified uses for this product are detailed in Section 1.2. |
|----------------------------|---|

STYCCOBOND F61

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

ETHYL ACETATE (CAS: 141-78-6)

DNEL

Industry - Inhalation; Short term systemic effects: 1468 mg/m³

Industry - Inhalation; Short term local effects: 1468 mg/m³

Consumer - Inhalation; Short term systemic effects: 734 mg/m³

Consumer - Inhalation; Short term local effects: 734 mg/m³

Industry - Inhalation; Long term local effects: 734 mg/m³

Industry - Dermal; Long term systemic effects: 63 mg/kg/day

Industry - Inhalation; Long term systemic effects: 734 mg/m³

Consumer - Dermal; Long term systemic effects: 37 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 367 mg/m³

PNEC

- Fresh water; 0.26 mg/l

- marine water; 0.026 mg/l

- Intermittent release; 1.65 mg/l

- Sediment (Freshwater); 1.25 mg/kg

- Sediment (Marinewater); 0.125 mg/kg

- Soil; 0.24 mg/kg

- STP; 650 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Personal protection

Always check applicability with your supplier of protective equipment.

Eye/face protection

If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

STYCCOBOND F61

| | |
|--|---|
| Hygiene measures | Provide eyewash station. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Do not smoke in work area. Good personal hygiene practices should be followed when working with chemicals. |
| Respiratory protection | Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. If exposure levels are exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used. Self-contained breathing apparatus must be available in case of emergency. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. |
| Environmental exposure controls | Keep container tightly sealed when not in use. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------------------|
| Appearance | Viscous liquid. |
| Colour | Brown. |
| Odour threshold | Not determined. |
| pH | pH (concentrated solution): N/A |
| Melting point | Not applicable. |
| Initial boiling point and range | Not determined. |
| Flash point | 1°C |
| Evaporation rate | Not determined. |
| Evaporation factor | Not determined. |
| Flammability (solid, gas) | Not determined. |
| Upper/lower flammability or explosive limits | Not determined. |
| Other flammability | Not determined. |
| Vapour pressure | Not determined. |
| Vapour density | Not determined. |
| Relative density | 0.9 @ 20°C |
| Bulk density | Not determined. |
| Solubility(ies) | Insoluble in water. |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | Viscous |
| Explosive properties | Not determined. |
| Explosive under the influence of a flame | Not considered to be explosive. |

STYCCOBOND F61

| | |
|--------------------------------------|--|
| Oxidising properties | Not determined. |
| Comments | Information given is applicable to the product in its ready-to-use form. |
| <u>9.2. Other information</u> | |
| Other information | None. |
| Refractive index | Not determined. |
| Particle size | Not applicable. |
| Molecular weight | Not determined. |
| Volatility | Not determined. |
| Saturation concentration | Not applicable. |
| Critical temperature | Not determined. |
| Volatile organic compound | No specific test data are available. |

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions In use may form flammable/explosive vapour-air mixture.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:
Oxidising materials.

10.5. Incompatible materials

Materials to avoid Flammable/combustible materials.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Acute toxicity - oral

Notes (oral LD₅₀) No specific test data are available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No specific test data are available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

STYCCOBOND F61

| | |
|--|---|
| Animal data | No specific test data are available. |
| Human skin model test | No specific test data are available. |
| Extreme pH | No specific test data are available. |
| <u>Serious eye damage/irritation</u> | |
| Serious eye damage/irritation | Irritation of eyes is assumed. |
| <u>Respiratory sensitisation</u> | |
| Respiratory sensitisation | No specific test data are available. |
| <u>Skin sensitisation</u> | |
| Skin sensitisation | Sensitising. |
| <u>Germ cell mutagenicity</u> | |
| Genotoxicity - in vitro | No specific test data are available. |
| Genotoxicity - in vivo | No specific test data are available. |
| <u>Carcinogenicity</u> | |
| Carcinogenicity | No specific test data are available. |
| IARC carcinogenicity | Not listed. |
| <u>Reproductive toxicity</u> | |
| Reproductive toxicity - fertility | No specific test data are available. |
| <u>Specific target organ toxicity - single exposure</u> | |
| STOT - single exposure | Not classified as a specific target organ toxicant after a single exposure. |
| <u>Specific target organ toxicity - repeated exposure</u> | |
| STOT - repeated exposure | May cause damage to organs through prolonged or repeated exposure. |
| Target organs | Respiratory system, lungs Skin |
| <u>Aspiration hazard</u> | |
| Aspiration hazard | Not relevant. |
| <u>General information</u> | |
| General information | Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. |
| Inhalation | Harmful: danger of serious damage to health by prolonged exposure through inhalation. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. |
| Ingestion | Unlikely to occur in normal use. |
| Skin contact | Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction. |
| Eye contact | Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. A single exposure may cause the following adverse effects: Corneal damage. |
| Acute and chronic health hazards | Contains a substance with possible risk of harm to the unborn child. May cause damage to organs through prolonged or repeated exposure. |
| Route of exposure | Inhalation Skin and/or eye contact |
| Target organs | Eyes Respiratory system, lungs Skin |

STYCCOBOND F61

| | |
|-------------------------------|--|
| Medical symptoms | Difficulty in breathing. Dryness and/or cracking. Intoxication. Irritation of eyes and mucous membranes. Nausea, vomiting. |
| Medical considerations | Chronic respiratory and obstructive airway diseases. Skin disorders and allergies. Pre-existing eye problems. |

Toxicological information on ingredients.

TOLUENE

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

ETHYL ACETATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 4,100.0

Species Mouse

ATE oral (mg/kg) 4,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

ATE dermal (mg/kg) 2,001.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

ATE inhalation (vapours mg/l) 30.0

Skin corrosion/irritation

Animal data Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity

STYCCOBOND F61

| | |
|---|---|
| Acute toxicity - fish | Not determined |
| Acute toxicity - aquatic invertebrates | Not determined. Highly insoluble in water. |
| Acute toxicity - aquatic plants | Not determined. Highly insoluble in water. |
| Acute toxicity - microorganisms | Not determined. Highly insoluble in water. |
| Acute toxicity - terrestrial | Not determined. Highly insoluble in water. |

Chronic aquatic toxicity

| | |
|--|-----------------|
| Chronic toxicity - fish early life stage | Not determined. |
| Short term toxicity - embryo and sac fry stages | Not determined. |
| Chronic toxicity - aquatic invertebrates | Not determined. |

Ecological information on ingredients.

ETHYL ACETATE

Acute aquatic toxicity

| | |
|---|--|
| Acute toxicity - fish | LC ₅₀ , 96 hours: 230 mg/l, NOEC, 32 days: >9.65 mg/l, |
| Acute toxicity - aquatic invertebrates | EC ₅₀ , 48 hours: 610 mg/l, Daphnia magna NOEC, 21 days: 2.4 mg/l, Daphnia magna |
| Acute toxicity - aquatic plants | EC ₅₀ , 48 hours: 5600 mg/l, Freshwater algae |

12.2. Persistence and degradability

| | |
|--------------------------------------|---|
| Persistence and degradability | There are no data on the degradability of this product. |
| Phototransformation | Not determined. |
| Stability (hydrolysis) | Highly insoluble in water. |
| Biodegradation | Not readily biodegradable. |
| Biological oxygen demand | No specific test data are available. |
| Chemical oxygen demand | No specific test data are available. |

Ecological information on ingredients.

ETHYL ACETATE

| | |
|--------------------------------------|---|
| Persistence and degradability | The product is readily biodegradable. |
| Biodegradation | - 79%: 20 days The substance is readily biodegradable. |

12.3. Bioaccumulative potential

| | |
|----------------------------------|---------------------------------------|
| Bioaccumulative potential | No data available on bioaccumulation. |
|----------------------------------|---------------------------------------|

STYCCOBOND F61

Partition coefficient Not determined.

Ecological information on ingredients.

ETHYL ACETATE

Bioaccumulative potential BCF: 30, Leuciscus idus (Golden orfe) The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Not determined.

Henry's law constant Not determined.

Surface tension Not determined.

Ecological information on ingredients.

ETHYL ACETATE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Adsorption/desorption coefficient Water - : 1.43 @ 25°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Should be disposed of as hazardous waste via a licensed waste operator.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

UN No. (ADN) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

STYCCOBOND F61

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

| | |
|-----------------------------|----|
| ADR/RID class | 3 |
| ADR/RID classification code | F1 |
| ADR/RID label | 3 |
| IMDG class | 3 |
| ICAO class/division | 3 |
| ADN class | 3 |

Transport labels



14.4. Packing group

| | |
|-----------------------|----|
| ADR/RID packing group | II |
| IMDG packing group | II |
| ICAO packing group | II |
| ADN packing group | II |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

| | |
|--|----------|
| EmS | F-E, S-D |
| ADR transport category | 2 |
| Emergency Action Code | •3YE |
| Hazard Identification Number (ADR/RID) | 33 |
| Tunnel restriction code | (D/E) |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|---|--|
| National regulations | No listing known. |
| Guidance | Safety Data Sheets for Substances and Preparations. |
| Authorisations (Annex XIV Regulation 1907/2006) | No specific authorisations are known for this product. |

STYCCOBOND F61

Restrictions (Annex XVII Regulation 1907/2006) No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

| | |
|---|---|
| General information | F.Ball and Company Ltd Technical Datasheet. |
| Key literature references and sources for data | Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits. |
| Revision comments | Section 8: update |
| Revision date | 25/06/2019 |
| Revision | 16 |
| Supersedes date | 17/08/2017 |
| SDS status | Approved. |
| Hazard statements in full | H224 Extremely flammable liquid and vapour. H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.