



# STYCCOCLEAN C140

## Floor Cleaner

## PRODUCT DATA

### INTRODUCTION

**STYCCOCLEAN C140** is a concentrated alkaline liquid detergent used as a cleaner for removing a wide range of contaminants including grease, oil and some adhesives. It can also be used for stripping emulsion based polish from floorcoverings.

STYCCOCLEAN C140 can be used for cleaning flooring grade asphalt, Tarmac, concrete, sand/cement screed, granolithic, ceramic, quarry tiles and terrazzo subfloors.

### APPLICATION

Dilute with three parts clean water. Apply to the floor area to be cleaned and leave for approximately 5 minutes then scrub. Remove the cleaner with a mop or if possible a wet vacuum, then rinse thoroughly with clean water. No trace of the cleaner must remain on the floor or floorcovering. The concentrated cleaner may be used to remove more resistant contamination. If the surface is heavily contaminated more than one application may be necessary.

### PRECAUTIONS

Avoid splashing the cleaner on skin, clothing, footwear, furniture or any other materials. Should this occur, wash off immediately with clean water. Wear suitable protective clothing, gloves and eye protection.

### TOOLS

Plastic bucket, stiff brush or scrubbing machine, mop or wet vacuum machine.

### STORAGE

Store between 5°C and 30°C. Protect from frost.

### SHELF LIFE

12 months in unopened containers and stored under good conditions.

### PACKAGES

5 litre bottle

### TECHNICAL INFORMATION

Colour	Yellow
Consistency	Liquid

### FEATURES

- Cleans a wide range of contaminants
- Suitable for use on a wide variety of floorcoverings
- Removes grease, oil and some adhesives
- Can be used for stripping emulsion based polish from floorcoverings

### HEALTH AND SAFETY ADVICE

This product is classified. Obtain the relevant Safety Data Sheet and follow the advice given.

These can be found at [www.f-ball.co.uk](http://www.f-ball.co.uk) alternatively these can be obtained from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Site conditions vary, to ensure this product is suitable and to confirm this data sheet is current please contact our Technical Service Department.

**For further information about F. Ball products or more detailed technical assistance, please contact:**

**F. Ball and Co. Ltd.**  
Churnetside Business Park  
Station Road, Cheddleton, Leek  
Staffordshire ST13 7RS  
United Kingdom

Tel: +44 (0) 1538 361633  
Fax: +44 (0) 1538 361622  
Tech Services Fax: +44 (0) 1538 361567  
Email: [mail@f-ball.co.uk](mailto:mail@f-ball.co.uk)  
[www.f-ball.co.uk](http://www.f-ball.co.uk)