

IMPACT TAPE

CONTACT ADHESIVE ON A ROLL

PRODUCT DATA SHEET
PUBLISHED JULY 2001

SITE CONDITIONS VARY, TO ENSURE THIS PRODUCT IS SUITABLE AND CONFIRM THIS DATA SHEET IS CURRENT, PLEASE CALL OUR TECHNICAL SERVICES DEPARTMENT.

PRODUCT DESCRIPTION - Double sided tape of pressure sensitive adhesive on a fine webbing carrier.

PRODUCT ADVANTAGES - Plasticiser resistant. Resistant to wet cleaning. Cost saving rapid application. Low odour. No health & safety hazard in normal use.

APPLICATIONS - For bonding a wide range of dimensionally stable smooth faced materials to wall surfaces of plaster, wood, concrete, metal and ceramic tiles.

SPECIFICATION - Tape width: 25mm, 50mm and 85mm.

Roll size: 50 metres.

Shelf life: 12 months in the original packaging stored under cool conditions.

APPLICATION TECHNIQUES - Surfaces must be **smooth**, clean, dry and **free of dust**. Very absorbent surfaces such as untreated plaster should be primed with STYCCOBOND F70.

Apply the tape directly to the material to be bonded.

Remove the release paper, position on the wall and **apply firm pressure** to obtain the maximum performance from the tape.

Corners and joints should be re-inforced by applying Impact Tape directly to the wall on all internal and external mitres. Cut the material to fit the mitre before fitting into position.

TOOLS - Hand roller.

Further information is available from Technical Service.



F. Ball and Co. Ltd.

Churnetside Business Park, Station Road, Cheddleton, Leek, Staffordshire. ST13 7RS, United Kingdom.

Tel: +44 (0) 1538 361633 Fax: +44 (0) 1538 361622

(For technical service enquiries only Fax: +44 (0) 1538 361567)

E mail: webmaster@f-ball.co.uk Internet: www.f-ball.co.uk

